



X120^{GO} Laser Scanner

3D Handheld
Laser Scanner



STONEX
SLAM
Scanning. Location. Mapping. SLAM.

X120^{GO} TECHNICAL FEATURES

The X120^{GO} is the latest generation system based on the SLAM technology, capable of covering any customer need. The range of up to 120 metres and a rotating head that maximises the coverage of the laser beam make it versatile for any environment. Equipped with 2 cameras and GNSS receiver for real-time point cloud colouring and orientation. The two cameras provide navigable and measurable panoramic cameras superimposed on the 3D model. The system allows for the survey of static scans in X-Whizz mode, automatically aligned to the SLAM survey. Backpack, shoulders hook, car mount and UAV mount for DJI M350 can complete the system.

LIDAR

| Sensor Model | Hesai XT16 | Hesai XT32 |
|--------------------------|--|--|
| Max Range | 120 m | |
| Min Range | 0.5 m | |
| Return number | 2 | |
| Scanning Point Frequency | 320.000 pts/s (single return) 640.000 pts/s (dual return) | 640.000 pts/s (single return) 1.280.000 pts/s (dual return) |
| Field of view | 360° x 290° | |
| Laser Class | Class 1 eye-safe per IEC/EN 60825-1:2014 | |
| Channels | 16 | 32 |
| Wavelength | 905nm | |

COLOR CAMERA

| | |
|--------------|---------------------------------|
| Nº of pixels | 24 Mpx (2 cameras, 12 Mpx each) |
| Diagonal FOV | 210° |
| Focal length | 1.26 mm |
| Resolution | 4000x3000 px |
| Sensor size | 1/2.3 inch |
| Pixel size | 1.55 μ m |

GNSS RECEIVER

| | |
|----------------------|---|
| Satellites Signal | GPS L1 C/A/L2P(Y)/L2C/L5 GLONASS L1/L2 Galileo E1/E5a/E5b BDS B1I/B2I/B3I QZSS L1/L2/L5 |
| DGPS (RMS) | Horizon. 0.4 m+1 ppm Vertical 0.8 m+1 ppm |
| RTK (RMS) | Horizon. 0.8cm+1ppm Vertical 1.5cm+1ppm |
| Speed accuracy (RMS) | 0.03m/s |

1. Environment dependent

2. Any CPU, only NVIDIA GPU

3. SLAM only, no external platforms

SYSTEM

| | |
|-----------------------|--|
| Relative accuracy | Up to 6mm ¹ |
| Global accuracy | Up to 2cm ¹ |
| | 5cm on UAV platform ¹ |
| Control point support | Ground & wall |
| Data storage | 512GB SSD |
| Communication | Wi-fi, Bluetooth, USB type-c, Lemo connector |
| Operating mode | SLAM & X-Whizz modes, real-time visualisation (colored and oriented) |
| Processing mode | Real-time processing Post-processing with GOpost ² |

ELECTRICAL SPECIFICATION

| | |
|-----------------------------|------------------------|
| Power consumption | 26W |
| System supply voltage | 20V |
| Operating time ³ | 1.2 h (single battery) |
| External power | USB type-c |
| Battery input voltage | 5-20V |
| Battery output voltage | 10.8V |
| Battery capacity | 3000mAh |

PHYSICAL SPECIFICATION

| | |
|-----------------------|---|
| Weight | 1.6 kg (without battery) 2.1 kg (with battery) |
| Size | 404 mm x 170mm x 188mm |
| Operating temperature | -20°C to +50°C (-4°F to 122°F) |
| Operating humidity | <95% |
| Waterproof/Dustproof | IP54 |

PLATFORM/EXTENSION

| | |
|---------------|--|
| Backpack | ✓ |
| GNSS module | Integrated |
| 360° camera | Integrated Insta X360 X4/X5/DJI Osmo360 |
| Vehicle mount | ✓ |
| UAV | DJI M300/350 |
| Radio Modem | Stonex SR02 |

BUNDLED SOFTWARE

GOapp



GOapp is a dedicated mobile application for Stonex SLAM scanners, to manage projects, real time point cloud display, image preview, firmware upgrade and other operations. The APP runs on Android and iOS operating system.

GOpost



Windows post processing software which performs optimization processing, colouring of point clouds and creation of panoramic images. You can also import control points to georeference the point cloud.



Illustrations, descriptions and technical specifications are not binding and may change

STONEX AUTHORIZED DEALER

STONEX®

Viale dell'Industria 53 - 20037 Paderno Dugnano (MI) - Italy
Phone +39 02 78619201
www.stonex.it | info@stonex.it